

# KNOW-HOW FOR GAS ASSISTED INJECTION MOULDING TECHNOLOGY



## CONTACT DETAILS:

Research Results Transfer Office-  
OTRI  
University of Alicante  
Tel.: +34 96 590 99 59  
Email: [areaempresas@ua.es](mailto:areaempresas@ua.es)  
<http://innoua.ua.es>

## ABSTRACT

In Gas-Assisted Injection Moulding (GAIM), gas is injected into a mould that has been partially filled with polymer. The gas drives the molten polymer core further into the mould, until it is filled completely. The penetrating gas leaves behind a polymer layer at the mould walls, yielding a product with a polymer skin and an inner gas channel. GAIM offers a number of advantages over conventional injection moulding. They mainly originate from the negligible pressure drop in the gas core: reduced clamp force, reduced sink marks, reduced residual stresses and shorter cycle times. The Chemical Engineering Department of the University of Alicante has applied successfully a complete CAE software package in order to give mould design guidelines and select the optimum process conditions. We are seeking companies to provide us our high experience, expertise and know-how to produce parts that demands the best quality.

## ADVANTAGES AND INNOVATIVE ASPECTS

### ADVANTAGES

Some of the potential benefits of gas-assist injection moulding are:

- Use of lower tonnage machines
- Lower injection pressures
- Improved part quality
- Reduced cycle time vs solid sections
- High strength to weight ratio
- Reduced/eliminated sink
- Less warpage
- Low moulded-in stress provides excellent dimensional stability
- Design flexibility
- Reduced tooling costs as a result of replacing hot runner systems with gas channels.

### INNOVATION ASPECTS

Nowadays, commercial packages of Computer Simulation of Gas-Assisted Injection Moulding are available only for thin-walled moulded parts, which are simulated using a midplane model (2½D Hele-Shaw approach). Consequently, it is necessary to create a midplane representation of the complex thick mould cavity. However, for thick parts a midplane representation involves a considerable geometric simplification. Moreover, in some areas of the part it does not exist a unique midplane representation.

A methodology to choose the midplane representation which best fit with the results provided by a three-dimensional computer analysis of the filling stage (conventional moulding) performed with a 3D CAD model of the complex part has been developed and tested.

## MARKET APPLICATIONS

Initial applications in gas-assist injection moulding were primarily closed channel parts such as automobile grab handles and lawn and garden furniture handles. As the technology has sophisticated, design techniques were applied to gas-assist injection moulding, the variety and complexity of applications increased. Next table list examples of these products

**Table 1.** Gas-Assist Injection Moulding

- Appliance handles
  - Toy industry
  - Automotive
    - accelerator pedal arms
    - air filter housings
    - door handles
    - mirror housings
    - oil filler duct
  - Business machine chassis / housings
  - Furniture: chairs, tables
  - Television housings
  - Golf club shafts
  - Basketball backboards
  - CD-ROM trays
  - Bottle crates
  - Copier panels
  - Shower heads
  - Washing machine agitators
  - Window frames
- 

## COLLABORATION SOUGHT

Two types of cooperation are sought by the Department of Chemical Engineering of the University of Alicante:

- Consulting services for companies which are working or expect to work with GAIM.
  - Instruct people interested in perform the tasks involved in gas assisted injection moulding.
-